

CYBOX AP 2

RAILWAY ACCESS POINT WITH WI-FI 5 DUAL RADIO

ELTEC

systems

DESCRIPTION

System Architecture	Dual-Core CPU T1023, 1200 MHz 1 GB RAM, 128 MB Flash
Power Supply	24 to 110 VDC, wide-range power supply (compliant to EN 50155)
Ambient Temperature	depending on temperature class of Wi-Fi module Class OT4, -40.. +70 °C (85 °C) operating or Class OT3, -25.. +70 °C (85 °C) operating -40.. +85 °C storage
Standards	EN 50155

STANDARD CONFIGURATIONS

ORDER NO.	LAN 1 (M12 X-coded)	LAN 2 (M12 X-coded)	Ethernet Switch	Wi-Fi 1 802.11ac 3x3 MIMO	Wi-Fi 2 802.11ac 3x3 MIMO	Input PSU 24 – 110 VDC (M12 A-coded)	Input PoE on LAN 1	USB 2.0/RS232 (M12 8-pin A-coded)	Bypass Relays	Antenna Connectors	Antenna Combiners	IP Class
CYAPW-1050V0	1 Gbit	1 Gbit	-	●	●	●	●	●	-	6x QLS	-	IP40
CYAPW-1053V0	1 Gbit	1 Gbit	-	●	●	●	-	●	●	6x QLS	-	IP40
CYAPW-1061V0	1 Gbit	1 Gbit	●	●	●	●	●	●	-	6x QLS	-	IP40
CYAPW-1062V0	1 Gbit	1 Gbit	●	●	●	●	-	●	●	6x QLS	-	IP40
CYAPW-1200V0	1 Gbit	1 Gbit	-	●	●	●	●	●	-	3x QLS	●	IP40
CYAPO-2000V0	1 Gbit	1 Gbit	-	●	●	●	●	●	-	6x N-Type	-	IP67

Further information on www.eltec.com

ELTEC Elektronik AG
Galileo-Galilei-Str. 11
55129 Mainz
Germany

FON +49 6131 918 100
FAX +49 6131 918 195
EMAIL info@eltec.com
WWW eltec.com

Copyright © 2021 by ELTEC Elektronik AG, Mainz.
All trademarks are the property of their owners. All rights reserved.

Revision: **1.3** | Date: **28.03.2022**