

CYBOX RT 3

RAILWAY ROUTER WITH 5G AND WI-FI 5 WAVE 2

ELTEC

systems

DESCRIPTION

System Architecture	Dual-Core CPU T1023, 1200 MHz 1 GB RAM, 128 MB Flash
Power Supply	24 to 110 VDC, wide-range power supply (compliant to EN 50155)
Ambient Temperature	depending on temperature class of Wi-Fi module Class OT4, -40.. +70 °C (85 °C) operating or Class OT3, -25.. +70 °C (85 °C) operating -40.. +85 °C storage
Standards	EN 50155

STANDARD CONFIGURATIONS

ORDER NO.	LAN 1 (M12 X-coded)	LAN 2 (M12 X-coded)	5G	LTE Cat-18	Wi-Fi 802.11ac Wave 2 4x4 MU-MIMO	Input PSU 24 – 110 VDC (M12 A-coded)	Input PoE+ on LAN 1	USB 2.0/RS232 (M12 8-pin A-coded)	GNSS	Ethernet Switch	Bypass Relays	Antenna Connectors	Antenna Combiners	IP Class
CYRTW-3010V0	1 Gbit	1 Gbit	●	-	●	●	●	●	●	-	-	9x QLS	-	IP40
CYRTW-3011V0	1 Gbit	1 Gbit	●●	-		●	●	●	●	-	-	9x QLS	-	IP40

Further information on www.eltec.com

ELTEC Elektronik AG
Galileo-Galilei-Str. 11
55129 Mainz
Germany

FON +49 6131 918 100
FAX +49 6131 918 195
EMAIL info@eltec.com
WWW eltec.com

Copyright © 2021 by ELTEC Elektronik AG, Mainz.
All trademarks are the property of their owners. All rights reserved.

Revision: **1.4** | Date: **30.03.2022**